

Cree® RSW Series

LED Street Luminaire



HELLO, MEET THE WARMER SIDE OF COOL

Unrivaled Visual Comfort

Forget just illuminating your streets. We want to enhance the experience of those who live under your lights. The RSW Series, with WaveMax® Technology, reduces glare while delivering optimized target illumination and industry-leading efficacy — up to 127 Lumens Per Watt — to improve overall energy efficiency. Finally, a high efficacy LED Street light offered in both warmer (2700K or 3000K) or cooler color temperatures (4000K or 5000K) with excellent color rendering (CRI up to 80).

Reliable Savings

Street lighting is a significant investment and it's critical to select the right partner. Cree is the industry leader that designed and manufactured the first LED street light. With unmatched experience and a culture built around innovation, we continue to create products that reliably provide significant energy savings (up to 70% compare to traditional technology) and maintenance savings that shortens paybacks to put more money back into your budget sooner.

Easy Advantage

Keeping the installer in mind, we've designed the RSW Series to be easy to install with features like tool-less entry, straight in wiring, bubble level, and adjustable mounting. This lightweight luminaire is constructed of non-conductive, high strength bulk molding compound for durability and installer safety. Plus, it's backed by our industry-leading 10-year limited warranty.

CREE 

REDEFINING THE EXPECTATIONS OF STREET LIGHTING

The RSW Series is a new family of street lights that directly address brightness and glare concerns for cities across the country. Cities and municipalities originally adopted LED lighting that utilized mostly cool white technology to help achieve an attractive ROI. Now, with WaveMax® Technology, the RSW™ LED street light provides an opportunity to utilize warm color temperatures without sacrificing efficiency or reliability.

PERFORMANCE SUMMARY
Input Power: 26W-53W (Small); 75W-93W (Medium)
Efficacy: Up to 127 Lumens per Watt (LPW)
CRI: 70 CRI (3000K, 4000K & 5000K); 80 CRI (2700K, 3000K, 4000K)
CCT: 2700K, 3000K, 4000K, 5000K
Input Voltage: 120-277V, 50/60Hz
Weight: Small 8.45 lbs (3.8kg); Medium 13.8 lbs (6.3kg)
Dimensions: Small 20.7"L x 9.8"W x 4.7"H; Medium 25.2"L x 11.3"W x 5.6"H (includes NEMA® Receptacle)
Limited Warranty†: 10 years on luminaire


PRODUCT COMPARISON				
Data	RSW Series Small	High Pressure Sodium 70W	RSW Series Medium	High Pressure Sodium 150W
CRI	70 or 80	22	70 or 80	70
CCT	2700K; 3000K; 4000K; 5000K	2100K	2700K; 3000K; 4000K; 5000K	4000K
Weight	8.45 lbs.	30 lbs.	13.8 lbs.	12 lbs.
Warranty	10 Years	5 Years (electrical) 1 Year (paint)	10 Years	5 Years
System Watts	30 50	105	90	27
Efficacy (LPW)	127 122	44	127	97

APPLICATIONS



Street Lighting

Virtually maintenance-free, the RSW™ LED Street Luminaire is designed to last 100,000 hours. Now, maintenance crews can focus on more important projects than replacing lamps.




Campus Street Lighting

Welcome visitors to your site with either warm CCT that provides a warm and inviting lighting experience or cool CCT that brings the beauty of the architecture and surrounding areas to the forefront.



Residential Street Lighting

Rest assured that the RSW luminaire will make the transition to LED a warm and inviting one. With warm CCTs, the familiar color will go unchanged while delivering up to 130 lumens per watt to the streets.



Intersections

Accidents happen, but we're here to help reduce them at busy intersections. With improved visibility at 80 CRI, you can see nearby vehicles and surrounding areas better to avoid unsafe situations.

ORDERING INFORMATION

Example: RSW5-A-HT-2ME-3L-30K7-UL-GY-N

Product	Version	Mounting	Optic	Lumen Output	CCT & CRI	Voltage	Color	Utility Label/Receptacle
RSWS Small	A	HT Horizontal Tenon	2ME Type II Medium	3L 3,300 Lumens	27K8 2700K, 80 CRI 30K7 3000K, 70 CRI 30K8 3000K, 80 CRI 40K7 4000K, 70CRI 40K8 4000K, 80 CRI 50K7 5000K, 70CRI 50K8 5000K, 80 CRI	UL Universal 120-277V	GY Grey	N Utility Label and NEMA® Photocell Receptacle - External wattage label per ANSI C136.15 - 7-pin receptacle per ANSI C136.41 - Factory connected 0-10V dim leads - Photocell and shorting cap by others
			2LG Type II Long	5L 5,000 Lumens				
RSWM Medium			3ME Type III Medium	9L 9,500 Lumens				

Product specifications subject to change at any time. Visit www.cree.com/canada to find the most up-to-date information.

Visit www.cree.com/canada or contact a Cree lighting representative to learn more

creelightingcanada@cree.com | 800.473.1234

© 2017 Cree, Inc. All rights reserved. For informational purposes only. Not a warranty or specification. See www.cree.com/canada for warranty and specifications. Cree® and WaveMax® are registered trademarks, and RSW™ and the Cree logo are trademarks of Cree, Inc. NEMA® is a registered trademark of the National Electrical Manufacturers Association. CAT/SSHT-C039 Rev. Date: 04/14/17

