

Locked Lumen Output

For use with RSW™ LED Street and Area Luminaires -Small

Description:

The Locked Lumen Output option on this page permanently locks the lumen output on the RSW Series street and area luminaire to the setting selected. When ordered with the X option, the luminaire will be shipped from the factory at the lumen output setting selected, and will include a wattage label that indicates the wattage of the setting selected. When this option is selected, the luminaire output is not able to be adjusted in the field.

RSW™ Street Luminaires – 3L

| X Option Setting | CCT/CRI | System Watts | Label Wattage | Lumen Values | | Optics Qualified on DLC QPL |
|------------------|---------|--------------|---------------|----------------|-------|-----------------------------|
| | | 120-277V | | 2LG, 2ME & 3ME | w/BLS | |
| X3 | 27K8 | 26 | 30 | 2,756 | 2,547 | N/A |
| | 30K7 | 23 | 20 | | | |
| | 30K8 | 25 | 30 | | | |
| | 40K7 | 21 | 20 | | | |
| | 40K8 | 23 | 20 | | | |
| | 50K7 | 21 | 20 | | | |
| | 50K8 | 23 | 20 | | | |
| X2 | 27K8 | 20 | 20 | 2,169 | 2,004 | N/A |
| | 30K7 | 17 | 20 | | | |
| | 30K8 | 19 | 20 | | | |
| | 40K7 | 16 | 20 | | | |
| | 40K8 | 18 | 20 | | | |
| | 50K7 | 16 | 20 | | | |
| | 50K8 | 17 | 20 | | | |
| X1 | 27K8 | 15 | 20 | 1,633 | 1,509 | N/A |
| | 30K7 | 13 | 10 | | | |
| | 30K8 | 15 | 20 | | | |
| | 40K7 | 12 | 10 | | | |
| | 40K8 | 14 | 10 | | | |
| | 50K7 | 12 | 10 | | | |
| | 50K8 | 13 | 10 | | | |

Rev. Date: V1 04/21/2017



For use with RSW™ LED Street and Area Luminaires - Small

Description:

The Locked Lumen Output option on this page permanently locks the lumen output on the RSW Series street and area luminaire to the setting selected. When ordered with the X option, the luminaire will be shipped from the factory at the lumen output setting selected, and will include a wattage label that indicates the wattage of the setting selected. When this option is selected, the luminaire output is not able to be adjusted in the field.

RSW™ Street Luminaires – 5L

| X Option Setting | CCT/CRI | System Watts | Label Wattage | Lumen Values | | Optics Qualified on DLC QPL |
|------------------|---------|--------------|---------------|----------------|-------|-----------------------------|
| | | 120-277V | | 2LG, 2ME & 3ME | w/BLS | |
| X3 | 27K8 | 49 | 50 | 4,654 | 4,310 | N/A |
| | 30K7 | 41 | 40 | | | |
| | 30K8 | 46 | 50 | | | |
| | 40K7 | 38 | 40 | | | |
| | 40K8 | 43 | 40 | | | |
| | 50K7 | 38 | 40 | | | |
| | 50K8 | 41 | 40 | | | |
| X2 | 27K8 | 42 | 40 | 4,105 | 3,801 | N/A |
| | 30K7 | 36 | 40 | | | |
| | 30K8 | 40 | 40 | | | |
| | 40K7 | 33 | 30 | | | |
| | 40K8 | 38 | 40 | | | |
| | 50K7 | 33 | 30 | | | |
| | 50K8 | 36 | 40 | | | |
| X1 | 27K8 | 36 | 40 | 3,617 | 3,350 | N/A |
| | 30K7 | 30 | 30 | | | |
| | 30K8 | 34 | 30 | | | |
| | 40K7 | 28 | 30 | | | |
| | 40K8 | 32 | 30 | | | |
| | 50K7 | 28 | 30 | | | |
| | 50K8 | 30 | 30 | | | |