

CS/LS Series Accessories

Mounting Options for CS/LS Series Linear Luminaires

| Qty. | AC5-12/3-48-Q14B-JB 5" Cable Canopy with 48" #12/3 SJT Cord, Q14B Gripper, J-box strap | Qty. | AC5-18/5-48-Q14B-JB 5" Cable Canopy with 48" #18/5 SJT Cord, Q14B Gripper, J-box strap |
|---|---|---|---|
| <p>*Cable Length + 6.0" (152mm) MIN 90°C SUPPLY CONDUCTORS MAX 20 AMPS</p> | | <p>*Cable Length + 6.0" (152mm) MIN 90°C SUPPLY CONDUCTORS MAX 20 AMPS</p> | |
| Power Feed with Cable Support for use with single or row mounted luminaires for non-dimming applications. | | Power Feed with Cable Support for use with single or row mounted luminaires for dimming applications. | |

Ordering Information

Enter Custom Orders Below:

| Qty. | Type | Power Drop | Length | Connector to Luminaire | Connector to Ceiling | Options |
|------|---|--|---|---|--|------------------------------|
| | AC5 Adjustable Cable 5" Canopy | Blank No Power Drop Provided | # Cable Length in 24-inch increments (48" or 24" standard as shown) | Blank No Connector Provided Q14B 1/4 IP Gripper (bottom feed) | JB J-Box Strap Provided TB T-Bar Clamp Provided (not for use when power drops are provided) | Blank Color: White |
| | AC2 Adjustable Cable 2" Canopy (power drop not available) | | | | | |
| | PC5 Adjustable Power Cord 5" Canopy (no aircraft cable) | | | | | |
| | AC Adjustable Cable (no canopy) | Blank No Power Drop Provided | | | LP Cable Loop Provided | Blank Color: White |
| | TM (for CS Series only) Plastic Tong Hanger (24-pack) Pair supplied with each fixture. | | | | | |
| | TMM (for CS Series only) Metal Tong Hanger (pair). Recommended for surface mount. | | | | | |
| | LS4TWK (for LS Series only) Includes (3) #12AWG 54" (1372mm) Wires for Line (black), Neutral (white), Ground (green), (2) #18AWG 54" (1372mm) Wires for 0-10V Dimming (purple, gray) and (10) Wire Nuts | | | | | |
| | LS8TWK (for LS Series only) Includes (3) #12AWG 102" (2591mm) Wires for Line (black), Neutral (white), Ground (green), (2) #18AWG 102" (2591mm) Wires for 0-10V Dimming (purple, gray) and (10) Wire Nuts | | | | | |

Maximum number of allowable luminaires connected to a single Power Feed:

| 12AWG Input Power Feed on 20 amp circuit (limited to 16A per NEC) | | | | 18AWG Input Power Feed on 10 amp circuit (limited to 8A per NEC) | | | |
|---|--|--|--|--|--|--|---|
| CS Series 4' | LS Series 4' | CS Series 8' | LS Series 8' | CS Series 4' | LS Series 4' | CS Series 8' | LS Series 8' |
| 4' Fixtures: 120V: 43 fixtures 277V: 100 fixtures | 4' Fixtures: 120V: 39 fixtures 277V: 91 fixtures | 8' Fixtures: 120V: 23 fixtures 277V: 53 fixtures | 8' Fixtures: 120V: 19 fixtures 277V: 45 fixtures | 4' Fixtures: 120V: 21 fixtures 277V: 50 fixtures | 4' Fixtures: 120V: 19 fixtures 277V: 45 fixtures | 8' Fixtures: 120V: 11 fixtures 277V: 26 fixtures | 8' Fixtures: 120V: 9 fixtures 277V: 22 fixtures |



CS/LS Series Accessories

| | | |
|---|---|--|
| <p>Qty. AC5-48-Q14B-TB 5" Cable Canopy, 48" Cable, Q14B Gripper, T-bar clip</p> <p>AC5-48-Q14B-TB-50BULK 5" Cable Canopy, 48" Cable, Q14B Gripper, T-bar clip (50-Bulk Pack)</p> | <p>Qty. AC2-48-Q14B-TB 2" Cable Canopy, 48" Cable, Q14B Gripper, T-bar clip</p> <p>AC2-48-Q14B-TB-50BULK 2" Cable Canopy, 48" Cable, Q14B Gripper, T-bar clip (50-Bulk Pack)</p> | <p>Qty AC-144-Q14B-LP Adjustable 144" Loop Cable with Q14B Gripper</p> <p>AC-144-Q14B-LP-50BULK Adjustable 144" Loop Cable with Q14B Gripper (50-Bulk Pack)</p> |
| | | |
| <p>Qty. PC5-12/3-24-JB 5" Canopy with 24" #12/3 SJT Cord, J-box strap</p> | <p>Qty. PC5-18/5-24-JB 5" Canopy with 24" #18/5 SJT Cord, J-box strap</p> | <p>Qty. TM Plastic Tong Hanger (Pair) - For CS Series Only</p> |
| <p>*Cable Length + 6.0" MIN 90°C SUPPLY CONDUCTORS MAX 20 AMPS</p> | <p>*Cable Length + 6.0" MIN 90°C SUPPLY CONDUCTORS MAX 10 AMPS</p> | |
| <p>Power Feed with for use with single or row mounted luminaires for non-dimming applications.</p> | | <p>Dimming Control for use with Power Feed PC5-12/3-24-JB for selective luminaire dimming control in row configurations.</p> |
| <p>Qty. TMM Metal Tong Hanger (Pair) - For CS Series Only</p> | | |
| <p>0.433"</p> | | |

© 2015 Cree, Inc. and/or one of its subsidiaries. All rights reserved. For informational purposes only. Content is subject to change. Patent www.cree.com/patents. Cree® and the Cree logo, are registered trademarks of Cree, Inc. The UL logo is a registered trademark of UL LLC.

